

Führungsbahnabstreifer (FB)/Way Wipers (FB)



- entspannt gezeichnet / shown in relaxed position -

FB-A **A** **B** **L = 500 mm**

FB-A1	14	6,5
FB-A3	18	6,5
FB-A5	25	6,5
FB-A7	14	5
FB-A9	18	5
FB-A11	25	5

FB-B **A** **D** **L = 560 mm + 1000 mm**

FB-B1	9,5	5
FB-B3	15	7
FB-B5	18	9
FB-B7	21	7
FB-B9	25	11
FB-B11	26	7
FB-B15	31	7
FB-B19	39	7

FB-C **A** **E** **L = 800 mm**

FB-C1	29	15
FB-C5	34	15

Vorabstreifer
Spring steel
protection

FB-C **A** **D** **L = 800 mm**

FB-C3	25	12
FB-C7	30	12

FB-D1 **L = 850 mm**

Vorabstreifer
Spring steel
protection

FB-D3 **L = 850 mm**

FB-G **A** **D**

FB-G1	30	15,5
FB-G3	40	15,5

L = 500 mm

FB-E **A** **B**

FB-E1	25	2
FB-E5	34	2

L = 600 mm

FB-F3 **L = 1000 mm**

FB-U1 **L = 560 mm**

FB-U3 **L = 560 mm**
biegbar
flexible

FB-U5 **L = 560 mm**
biegbar
flexible

Federstahl
Spring steel

FB-U60 **L = 560 mm**

FB-U90 **L = 560 mm**

FB-M14 **L = 530 mm + 1000 mm**
Stainless steel

FB-M18 **L = 500 mm 1000 mm**
Edelstahl
Stainless steel

FB-M25 **L = 500 mm 1000 mm**
Edelstahl
Stainless steel

FB-M27 **L = 500 mm**
Andruckfedern
Pressure springs

FB-AW **A** **B** **D**

FB-AW1	18	7	10
FB-AW2	25	7	10

L = 1000 mm

FB-H1 **L = 500 mm**

FB-K **A** **D**

FB-K1	18	7,5
FB-K3	25	7,5

L = 500 mm

Alu

FB-N1 **L = 500 mm**

FB-V **A** **D**

FB-V1	18	7,5
FB-V3	18	7,5

L = 560 mm

Abstreifer (TA) / Wipers (TA)

- entspannt gezeichnet / shown in relaxed position -

	A	D	Länge/Length
TA-A1	15	6	500 mm
TA-A3	15	6	1000 mm
TA-A15			1000 mm

Späneschutz/Chip Protector
0,5 mm

TA-A5 L = 500 mm

Flachstahl/Steel insert
8 x 2 mm

TA-A7 L = 500 mm

Flachstahl/Steel insert
20 x 2 mm

TA-A30 L = 600 mm

TA-A40 L = 560 mm
TA-A42 L = 1000 mm

Ms/Brass

TA-A50 L = 1000 mm

Ms/Brass
10 x 2

	A	D	Länge/Length
TA-B1	18	6	500 mm
TA-B3	18	6	1000 mm
TA-B15			1000 mm

Späneschutz/Chip Protector
0,5 mm

TA-B5 L = 500 mm

Flachstahl/Steel insert
12 x 2 mm

TA-B7 L = 500 mm

Flachstahl/Steel insert
25 x 2 mm

	A	D	Länge/Length
TA-B9	20	5,5	500 mm
TA-B15			1000 mm

Späneschutz/Chip Protector
0,5 mm

	A	D	Länge/Length
TA-B11	20	5,5	500 mm
TA-B15			1000 mm

Späneschutz/Chip Protector
0,5 mm

Gleiter / Sliding shoes

TA-G1 L = 500 mm

	A	D	C
TA-G2	17	4	13
TA-G2.1	17	5	12

L = 1000 mm

TA-G6 L = 1000 mm

Dämpfer integriert
Bumper integrated

Ms/Brass

TA-C1.4 L = 1000 mm
Mantel/Carrier

Dämpfer
Bumper

TA-C1.5/1.6 L = 1000/3000 mm
Mantel/Carrier

TA-C2.5/2.6 L = 1000/3000 mm
Mantel/Carrier

Lippen/Lips
L = endlos/endless

Art. No.	Material
TA-C1.7	PU 83°, weiß, schwarz, rot
TA-C1.7	PU 83°, white, black, red
TA-C1.9	PU 95°, schwarz/black

	A	D	L = 1000 mm
TA-M			
TA-M1.0	16	~8	
TA-M2.0	21	~9	

Messingeinlage
Brass insert

TA-M3.0 L = 1000 mm

Späneschutz/Chip Protector

MS/brass

Dämpfer/Bumper

TA-C12 E / TA-C 15 E
Mantel/Carrier
L = 1000/3000 mm

TA-C13 E L = endlos/endless
Lippe/Lip

	A	D	L = 560 mm
TA-RA1	16	6	
TA-RA2	21	7	
TA-RA3	13	4	

06/2010